



Z H O N E

VDSL2 Bridged/Router

6652-A2

VDSL2 Bridged/Router 4-Port Modem

- ✓ *Programmable support of plan 997, 998, FX and China plan capable of supporting VDSL2 profiles 8a/b/c/d, 12a/b, 17a and 30a*
- ✓ *Optional U0 band for long reach applications*
- ✓ *DMT based packet mode supports Ethernet-over VDSL (EoVDSL) with asymmetric line data rates of 100Mbps downstream and 50Mbps upstream, or symmetric 50Mbps line data rate.*
- ✓ *Auto sensing ethernet ports*
- ✓ *Supports packet transfer mode with HDLC or EFM framing for EoVDSL*
- ✓ *Integrated Layer 2 switch with traffic classification and QoS support, including IP QoS based on IP, physical port*
- ✓ *IP routing, NAT, PAT, SPI firewall and packet filtering*

The 6652-A2 is an ethernet-over-VDSL bridge modem utilizing the Ikanos chipset that complies with various VDSL standards, and provides unprecedented broadband service over a single pair of copper wire. The four 10/100 Base-T Ethernet Ports can easily connect to any PC or LAN in a home or small office environment. Quality and multimedia service is ensured with its powerful traffic control and management over layer 2 or layer 3. While the NAT/PAT technologies share the broadband connection to all its LAN clients for all prevailing internet applications, the embedded firewall keeps out those malicious attacks and intrusions. Network management is implemented so it can be easily configured and managed by the service provider.

Technical Specifications

Dimensions

- W(10.03in) x D(6.29in) x H(1.65in)

Weight

- 0.75lbs

Power

- Input 120~240 VAC 50/60Hz
- Output 12VAC 1.5A

Interfaces

- 1 x RJ11 - VDSL2 uplink
- 1 x USB port
- 4 x RJ45 - 10Base-T/100Base-TX Ethernet
- 1 x ON/OFF Power Switch
- 1 x Reset

Standards Support

- VDSL
 - ITU-T G.993.2 (VDSL2)
 - ITU-T G.993.1 (VDSL1)
 - ANSI T1-424
 - ETSI TS 101 270-1
 - ETSI TS 101 270-2
 - China MII VDSL standard
 - ITU-T G.994.1 (G.hs) based hand shaking
 - Supports band plan 997, 998, FX and China
 - VDSL2 profiles 8a/b/c/d, 12a/b, 17a and 30a
 - EFM (IEEE802.3ah)
 - Extended USO band up to 276kHz
 - VLAN to Port mapping
- Ethernet Interface
 - IEEE 802.3/802.3u compliant
 - Support 10/100Mbps operation
 - Support half/full duplex operation
 - Support IEEE 802.3u clause 28-auto negotiation
 - Support Flow Control
 - Support Auto MDI/MDIX
 - IP Multicast and IGMP snooping
 - Support 802.1d
 - IEEE 802.1q
 - IEEE 802.1p
- Routing
 - Static routes
 - Dynamic routes: RIPv1 or RIPv2
 - PPP client
 - IGMP proxy
 - DHCP server and client
- Firewall
 - SPI firewall
 - Access control list based on IP and port
 - Port forwarding, virtual server
 - Support for one DMZ host
 - ALG support including FTP, PPTP, L2TP

Protocol Support

- ITU-T G.993.2
- ITU-T G.993.1
- ANSI T1.424
- ETSI TS 101 270-1
- ETSI TS 101 270-2
- RIPv1
- RIPv2
- UPnP
- IGMP proxy

Management

- Web Interface HTTP
- Telnet
- CLI

Regulatory Compliance

- FCC Part 15/68
- UL
- CSA
- CE
- RoHS Compliant

Operating Requirements

- Temperature
 - Operating: 0C to 40C / 32F to 104F
 - Non-Operating: -25C to 85C / -13F to 185F
- Humidity
 - Operating: 5% to 95% Relative Humidity (Non-Condensing)
 - Non-Operating: 5% to 95% Relative Humidity (Non-Condensing)

Ordering Information

6652-A2-200	VDSL2+ 4 Port CPE5, NA
6652-A2-302	VDSL2+ 4 Port CPE5, EURO



Zhone Technologies, Inc.
 @ Zhone Way
 7001 Oakport Street
 Oakland, CA 94621
 510.777.7000 phone
www.zhone.com

For more information about Zhone and its products, please visit the Zhone Web site at www.zhone.com or e-mail info@zhone.com

Zhone, the Zhone logo, and all Zhone product names are trademarks of Zhone Technologies, Inc. Other brand and product names are trademarks of their respective holders. Specifications, products, and/or product names are all subject to change without notice.
 Copyright 2007 Zhone Technologies, Inc. All rights reserved.