

| | | 5GHz Outdoor APs / Routers | | | | 2.4GHz Outdoor APs / Routers | | |
|-------------------------|--|---|--|---|---|---|---|--|
| | | 802.11a/n APs / Routers | | | | | | |
| Model | | WNAP-7206 | WNAP-7300 | WNAP-7320 | WNAP-7350 | WNAP-6305 | WNAP-6308 | WNAP-6350 |
| Product Image | | | | | | | | |
| Operating Environment | | Outdoor / IP55 | Outdoor / IP55 | Outdoor / IP55 | Outdoor / IP67 | Outdoor / IP55 | Outdoor / IP55 | Outdoor / IP67 |
| Wireless | | Standard: IEEE 802.11a/n Max. Data rate: 150Mbps Number of Radios: 1 MIMO System: 1T1R Antenna: 15dBi FP / 1 x RP-SMA Max. TX Power: 27dBm | Standard: IEEE 802.11a/n Max. Data rate: 300Mbps Number of Radios: 2 MIMO System: 2T2R Antenna: 16dBi FP / 2 x RP-SMA Max. TX Power: 24dBm | Standard: IEEE 802.11a/n Max. Data rate: 300Mbps Number of Radios: 2 MIMO System: 2T2R Antenna: 14dBi dual-polarity FP Max. TX Power: 27dBm | Standard: IEEE 802.11a/n Max. Data rate: 300Mbps Number of Radios: 2 MIMO System: 2T2R Antenna: 2 x N(F) connector Max. TX Power: 27dBm | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps Number of Radios: 1 MIMO System: 1T1R Antenna: 12dBi FP / 1 x RP-SMA Max. TX Power: 27dBm | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps Number of Radios: 1 MIMO System: 1T1R Antenna: 1 x N(M) connector Max. TX Power: 23dBm | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps Number of Radios: 2 MIMO System: 2T2R Antenna: 2 x N(F) connector Max. TX Power: 27dBm |
| Hardware | | Network Interface: 1 x 100TX PoE: Private | Network Interface: 2 x 100TX PoE: Private | Network Interface: 1 x 100TX WAN 1 x 100TX LAN PoE: Private | Network Interface: 1 x 100TX WAN 1 x 100TX LAN PoE: Private | Network Interface: 1 x 100TX WAN 1 x 100TX LAN PoE: Private | Network Interface: 1 x 100TX PoE: Private | Network Interface: 1 x 100TX WAN 1 x 100TX LAN PoE: 802.3af |
| Wireless Operating Mode | | Access Point Client Bridge Repeater (WDS) Universal Repeater (AP+Client) WISP | | | | | | |
| Wireless Security | | WEP / WPA WPA / WPA2-PSK WPA / WPA2 802.1X WPS | | | | | | |
| WAN Mode | | Dynamic IP Static IP PPPoE / PPTP / L2TP | | | | | | |
| Advanced Features | | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM Firewall NAT VPN Passthrough SNMP Layer 3 Routing Max. Client: Wired: 60, Wireless: 25 802.11g Protection Operating Temperature: -30 ~ 70 °C Power System: 12V DC, 1A | Multiple SSID (Up to 16) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM Firewall NAT VPN Passthrough SNMP Layer 3 Routing Max. Client: Wired: unlimited, Wireless: 128 802.11g Protection Operating Temperature: -20 ~ 70 °C Power System: 15V DC, 0.8A | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 8 DHCP Server WMM Firewall NAT VPN Passthrough SNMP Layer 3 Routing Max. Client: Wired: 60, Wireless: 40 802.11g Protection Operating Temperature: -20 ~ 70 °C Power System: 24V DC, 0.5A | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 8 DHCP Server WMM Firewall NAT VPN Passthrough SNMP Layer 3 Routing Max. Client: Wired: 60, Wireless: 40 802.11g Protection Operating Temperature: -30 ~ 75 °C Power System: 48V DC, 802.3af/at PoE | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 8 DHCP Server WMM Firewall NAT VPN Passthrough SNMP Layer 3 Routing Max. Client: Wired: 30, Wireless: 20 802.11g Protection Operating Temperature: -20 ~ 70 °C Power System: 24V DC, 0.7A | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 8 DHCP Server WMM Firewall NAT VPN Passthrough SNMP Layer 3 Routing Max. Client: Wired: 60, Wireless: 40 802.11g Protection Operating Temperature: -30 ~ 75 °C Power System: 48V DC, 802.3af/at PoE | |

| | | 2.4GHz Indoor | | | | | | | | | | | | |
|-------------------------|--|---|---|---|---|---|---|---|---|---|--|---|--|---|
| | | 802.11b/g/n Routers | | | | | | 802.11b/g/n AP / Extenders | | | | Dual Band AP / Extenders | | |
| Model | | WNRT-300 | WNRT-300G | WNRT-617G | WNRT-617 | WNRT-627 | WNRT-633 | WNAP-1110 | WNAP-1120PE | WNAP-1260 | WNAP-W2200 | WNAP-C3220 | WDAP-C7400 | WDAP-C7200AC |
| Product Image | | | | | | | | | | | | | | |
| Operating Environment | | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor | Indoor |
| Wireless | | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps MIMO System: 1T1R Antenna: 2dB internal Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 20dBm Network Interface: 1 x 100TX PoE: - Mobile Network: - USB: mini-USB for power/charging | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps MIMO System: 1T1R Antenna: 2dB internal Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 20dBm Network Interface: 1 x 100TX PoE: - Mobile Network: UMTS/HSPA USB: USB for 3G dongle mini-USB for power/charging | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps MIMO System: 1T1R Antenna: 5dBi detachable 1 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 1 x 100TX WAN, 4 x 100TX LAN PoE: - Mobile Network: UMTS/HSPA/EVDO USB: USB for 3G dongle | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps MIMO System: 1T1R Antenna: 5dBi Omni f xed Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 1 x 100TX WAN, 4 x 100TX LAN PoE: - Mobile Network: - USB: - | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 5dBi Omni f xed Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 1 x 100TX WAN, 4 x 100TX LAN PoE: - Mobile Network: - USB: - | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 5-dBi detachable 2 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 20dBm Network Interface: 1 x 1000T WAN, 4 x 1000T LAN PoE: - Mobile Network: - USB: - | Standard: IEEE 802.11b/g/n Max. Data rate: 150Mbps MIMO System: 1T1R Antenna: 4dBi detachable 1 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 1 x 100TX PoE: Private Mobile Network: - USB: - | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 3dBi detachable 2 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 1 x 100TX PoE: - Mobile Network: - USB: - | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 2 x 2dBi internal Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 17dBm Network Interface: 1 x 100TX PoE: - Mobile Network: - USB: - | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 2 x 2-dBi Printed Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 20dBm Network Interface: 1 x 100TX PoE: 802.3af Mobile Network: - USB: 1 x USB Charger | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 2 x 2dBi internal Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 20dBm Network Interface: 1 x 1000T PoE: 802.3af Mobile Network: - USB: - | Standard: IEEE 802.11a/b/g/n Max. Data rate: 450+450Mbps MIMO System: 3T3R Antenna: 3 x 4.5dBi Dual Band Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 2.4G: 27dBm, 5G: 22dBm Network Interface: 2 x 1000T (1x 802.3at PoE/PD) PoE: 802.3at Mobile Network: - USB: - | Standard: IEEE 802.11a/b/g/n/ac Max. Data rate: 300+867Mbps MIMO System: 2T2R Antenna: 2.4G: 3dBi, 5G: 2.5dBi Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 2.4G: 22.5dBm, 5G: 22dBm Network Interface: 1 x 1000T (802.3at PoE/PD) PoE: 802.3at PoE PD Mobile Network: - USB: - |
| Wireless Operating Mode | | Access Point Client Bridge Repeater (WDS) Universal Repeater (AP+Client) WISP | | | | | | | | | | | | |
| Wireless Security | | WEP WPA / WPA2-PSK WPA / WPA2 802.1X WPS | | | | | | | | | | | | |
| WAN Mode | | Dynamic IP Static IP PPPoE / PPTP / L2TP | | | | | | | | | | | | |
| Advanced Features | | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 5V DC, Built-in Battery | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 5V DC, Built-in Battery | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 12V DC | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 9V DC | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 9V DC | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 9V DC | Multiple SSID (Up to 3) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 5V DC, 802.3af PoE | Multiple SSID (Up to 5) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: -10 ~ 45 °C Power System: Built-in Power supply | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 802.3af PoE | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 12V DC, 802.3af PoE | Multiple SSID (2.4G: 8/ 5G: 2) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: -10 ~ 45 °C Power System: 802.3at PoE PD | Multiple SSID (2.4G: 5/ 5G: 5) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 50 °C Power System: 802.3at PoE PD | |

| | | 2.4GHz / 5G Indoor | | | 2.4GHz Industrial | | |
|-------------------------|--|---|--|---|--|--|--|
| | | Dual Band Routers | | | Industrial Access Points | | |
| Model | | WDRT-750AC | WDRT-1200AC | WDRT-731U | IAP-2000PE | IAP-2001PE | IAP-2000PS |
| Product Image | | | | | | | |
| Operating Environment | | Indoor | Indoor | Indoor | Indoor / IP30 | Indoor / IP30 | Indoor / IP30 |
| Wireless | | Standard: IEEE802.11a/b/g/n/ac Max. Data rate: 300+433Mbps MIMO System: 2.4G: 2T2R/ 5G: 1T1R Antenna: 2.4G: 2.5dBi, 5G: 3.8dBi Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 2.4G: 18dBm (max.), 5G: 15dBm (max.) Network Interface: 1 x 100TX WAN, 4 x 100TX LAN PoE: - Mobile Network: - USB: - | Standard: IEEE802.11a/b/g/n/ac Max. Data rate: 300+867Mbps MIMO System: 2T2R Antenna: 2.4G: 1.8dBi, 5G: 3.8dBi Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 2.4G: 18.5dBm (max.), 5G: 15.5dBm (max.) Network Interface: 1 x 100TX WAN, 4 x 100TX LAN PoE: - Mobile Network: - USB: USB3.0 for storage/printer | Standard: IEEE 802.11a/b/g/n Max. Data rate: 300+300Mbps MIMO System: 2T2R Antenna: 5-dBi Omni f xed Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 17dBm Network Interface: 1 x 100T WAN, 4 x 100T LAN (1 for IPTV) PoE: - Mobile Network: - USB: USB for storage / printer | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 5dBi detachable 2 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 4 x 100TX PoE: 802.3af | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 5dBi detachable 2 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 4 x 100TX PoE: 802.3af | Standard: IEEE 802.11b/g/n Max. Data rate: 300Mbps MIMO System: 2T2R Antenna: 5dBi detachable 2 x RP-SMA Max. Range: Indoor: 100m, Outdoor: 300m Max. TX Power: 18dBm Network Interface: 4 x 100TX PoE Injector PoE: 802.3af PSE Mobile Network: - USB: - |
| Wireless Operating Mode | | Access Point Client Bridge Repeater (WDS) Universal Repeater (AP+Client) WISP | | | | | |
| Wireless Security | | WEP WPA / WAP2-PSK WPA / WPA2 802.1X WPS | | | | | |
| WAN Mode | | Dynamic IP Static IP PPPoE / PPTP / L2TP | | | | | |
| Advanced Features | | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 12V DC | Multiple SSID (2.4G: 3/ 5G: 3) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 45 °C Power System: 12V DC | Multiple SSID (Up to 2) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: 0 ~ 40 °C Power System: 12V DC | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: -10 ~ 60 °C Power System: 12 ~ 48V DC / 24V AC | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: -10 ~ 60 °C Power System: 12 ~ 48V DC / 24V AC | Multiple SSID (Up to 4) 802.1Q VLAN AP Isolation WDS Max. 4 DHCP Server WMM SPI Firewall DMZ IPSEC VPN PPTP VPN VPN Passthrough SNMP IAPP(Roaming) Operating Temperature: -10 ~ 60 °C Power System: 24 ~ 48V DC, 24V AC |